

GENERAL GAS LEAK DETECTORS

GRD-1000 / 2000

GRD-1000 : DC형 DC Type / GRD-2000 : AC형 AC Type

제품 사양 | SPECIFICATIONS

모델명 (Model Name)	GRD-1000	GRD-2000
대상 가스 (Detectable Gas)	LNG Natural gas, LPG LP Propane, Butane	
검지 방식 (Sensing Method)	Catalytic combustion, Diffusion type	
경보 농도 (Measuring Range)	LEL 20%	LEL 15%
응답 속도 (Response Time)	Within 20 seconds of detection	
사용 온도 범위 (Operating Temperature)	-20°C~40°C	-20°C~49°C
소비 전력 (Power Consumption)	1.2W	2.1W, Normal / 2.3W, Alarm
전원 (Power Supply)	DC 12~15V	220~240V (AC) 50/60Hz
경보 표시 (Alarm Signal)	Yellow lamp & Buzzer sound at 1m 70dB	Yellow lamp & Buzzer sound at 1m 70dB (at 3m 85dB)
출력 전압 (Output Voltage)	DC 7V Out	DC 10V Out
중량 (Weight)	104g	300g
외형 크기 (Dimensions)	75(W) x 75(H) x 40(D) mm	76(W) x 117(H) x 38(D) mm
연동 제품 (Application Actuator)	GRC-1525, GRV-1525 15A, 20A, 25A, 32A, 40A, 50A, 65A, 80A, 100A	



▶ GRD-1000



▶ GRD-2000

AGD-250TN

일산화탄소 CO DETECTOR

제품 사양 | SPECIFICATIONS

모델명 (Model Name)	AGD-250TN
대상 가스 (Detectable Gas)	Carbon monoxide gas
검지 방식 (Sensing Method)	Electro-chemical sensor
작동 온도 (Operation Temperature)	-20°C~50°C
작동 습도 (Operation Humidity)	RH 95%
사용 전압 (Power Supply)	AC 220V, 50/60Hz single / DC 12V (option)
소비 전력 (Power Consumption)	1.5W Max.
경보 신호 (Alarm Signal)	Adjustment range (1~1000ppm) 1st 100ppm, 2nd 200ppm
출력 신호 (Output Signal)	DC 12V, Relay contact (option)
외형 크기 (Dimensions)	76(W) x 118(H) x 37.5(D) mm
중량 (Weight)	Approx. 22.0g
설치 방법 (Installation Method)	Wall mounting type

